



SP-IP-PCON-4-DS



SP-IP-PCON-8-DS

Features

- Connects to IP cameras with up to 5MP resolution
- Multi protocol IP camera support
- Storage at H.264/MPEG-4 standard
- NTP, SADP, SMTP, NFS protocols
- Build in webinterface
- Allows seamless connection from the Spectator Communication Platform (SCP)

Specifications

Type	SP-IP-PCON-4-DS	SP-IP-PCON-8-DS
Max total IPCam bandwidth (Mbit/s)	16	8
Max outgoing bandwidth (Mbit/s)	20	80
Max decoding resolution	5 MP	
Video input	4 channels, 4CIF	8 channels, 4CIF
Audio Input	1 channel RCA (2Vp-p, 1kΩ), for voice talk	
Audio output	1 channel RCA (600Ω)	
Video output	VGA, HDMI	
	Supported resolutions (VGA/HDMI) 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
Playback resolution	2560 × 1920, 2048 × 1536, UXGA, 1080P, 720P, 4CIF, VGA, DCIF, 2CIF, CIF, QCIF	
Synchrone playback	4-ch	8-ch
Communication interface	1 RJ-45 10/100/1000Mbps ethernet port	
	1 RS-485 interface	
HDD SATA interface	1 HDD (4TB max)	2 HDD (4TB each)
USB interface	2 USB 2.0	
Power supply	12VDC with supplied external adaptor (PSU 100 - 240VAC, 50 / 60 Hz)	
Power consumption	<10W (without HDD)	
Operating temperature	-10 °C ~ +55 °C	
Operating humidity	10% ~ 90%	
Dimensions (W x D x H)	315 x 230 x 45 mm	445 x 290 x 45 mm
Weight	< 2kg (without HDD)	

Delivery Package

- IP Protocol Converter
- Optical mouse
- HDD fixing screws
- External power supply

Ordering Information

- SP-IP-PCON-4-DS
- SP-IP-PCON-8-DS



SPECTATOR
VIDEO TECHNOLOGY

Nieuwstraat 2,
4921 CX Made,
The Netherlands